

# Test Report

Report No.: SHT09011400125

Page 1 of 5

**Client** : NANTONG GOLDEN PHOENIX TOY MANUFACTURING CO.LTD.  
**Address** : NO. 869 NANYUAN MIDDLE ROAD QIDONG CITY JIANGSU CHINA

**Report on the submitted sample said to be:**

Sample Name : Black Yellow Cheerleader  
Item No. : 20190  
Quantity of Sample : 3  
Exported to : U.S.A  
Labelled Age Grading : Over three  
Age Group Applied in Testing : Over 3 years  
Sample Received Date : Jan.14, 2009  
Sample Tested Date : Jan.14, 2009 to Feb.02, 2009

**TEST REQUEST**

- 1)ASTM F963-07<sup>e1</sup> Standard Consumer Safety Specification for Toy Safety
- 2)US Consumer Products Safety Improvement Act 2008 (CPSIA)(H.R. 4040)  
- Lead Content Test

**CONCLUSION**

**PASS**

**PASS**

**Test Results:** Please refer to next page(s)

Inspected by: Boly  
Engineer

Approved by: Victor wang  
Victor wang  
Lab Manager

Approved date: 2009-02-02  


# Test Report

Report No.: SHT09011400125

Page 2 of 5

**ASTM F963 –07<sup>e1</sup>**

AS SPECIFIED IN ASTM F963-07<sup>e1</sup> STANDARD CONSUMER SAFETY SPECIFICATION FOR TOY SAFETY.

<u>Clause</u>	<u>Description</u>	<u>Assessment</u>
4.	Safety Requirements	
4.1	Material Quality **.....	Pass
4.2	Flammability Test.....	N/A (See Note 1)
4.3	Toxicology	
4.3.5	Paint & Similar Surface-coating Material.....	Pass (See Note 2)
4.6	Small Objects.....	N/A
4.7	Accessible Edges.....	Pass
4.9	Accessible Points.....	Pass
5.	Safety Labeling Requirements	
5.2	Age Grading Labeling.....	Pass
7.	Producers Markings	
7.1	Producers Markings.....	Pass
8.	Test Method	
8.5	Normal Use Testing.....	Pass
8.7	Impact Test .....	Pass
8.8	Torque Test.....	Pass
8.9	Tension Test.....	Pass

\*\*Visual Examination

N/A = Not Applicable

Note 1:

Flammability Test (Clause 4.2)

Flammability Test on Textile Materials .....N/A

The samples are exempt from 16CFR 1610.1(d)(1):plain surface fabric with weight>2.6oz/sq.yd.

N/A = Not Applicable

Building C, Hongwei Industrial Zone, Baoan 70 District, Shenzhen

# Test Report

Report No.: SHT09011400125

Page 3 of 5

Note 2 :

**ASTM F963-07<sup>e1</sup> CLAUSE 4.3.5 - PAINT & SIMILAR SURFACE-COATING MATERIAL**

Heavy Metals Analysis : Total Lead (Clause 4.3.5.1)

Acid Digestion Method was Used and Total Lead Content was Determined by Inductively Coupled Plasma Optical Emission Spectrometer (ICP-OES).

<u>Element</u>	<u>Result(mg/kg)</u>	<u>Limit</u>
	Black coating(label)	(mg/kg)
Total Lead	< 5	600

Heavy Metals Analysis : Soluble Heavy Metal (Clause 4.3.5.2)

Acid Extraction Method was Used in accord with ASTM F963-07<sup>e1</sup> (Clause 8.3) and Toxic Elements Content were Determined by Inductively Coupled Plasma Optical Emission Spectrometer (ICP-OES).

Remark:

- < = Less than
- mg/kg = Milligram per kilogram based on dry weight of sample
- As received, the test portion of black coating(label) is less than 10mg, therefore such components were not tested for soluble elements, as specified in ASTM F963-07<sup>e1</sup> Clause 8.3.3.1 (2)

Note:

- Only applicable clauses were shown.

# Test Report

Report No.: SHT09011400125

Page 4 of 5

## 2) LEAD CONTENT TEST

As Specified in Consumer Products Safety Improvement Act 2008 (CPSIA)(H.R. 4040) and Title 16 Part 1303 Code of Federal Regulations, Chapter II – Consumer Products Safety Commission of U.S.A, Acid Digestion Method was Used and Total Lead Content was Determined by Inductively Coupled Plasma Optical Emission Spectrometer (ICP-OES).

### 1. Lead content in surface coating(s) and similar materials

Element	Result (ppm)	Required Limit <sup>#1</sup>
	(1)	(ppm)
Total Lead	<5	600

### 2. Lead content in other materials

Element	Result (ppm)												Required Limit <sup>#2</sup>
	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(ppm)
Total Lead	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	600

Tested Components:

- (1) Black coating(label)
- (2) Lt. yellow thread(pants)
- (3) Yellow fabric (Pants )
- (4) White elastic cord
- (5) Black velcro
- (6) Yellow/white belt
- (7) Yellow thread
- (8) Black fabric(cloth)
- (9) Black thread
- (10) Black ribbon(skirt)
- (11) White fabric(label)
- (12) White fabric
- (13) White ribbon(Pants)

Remark:

- < = Less than
- ppm= parts per million based on dry weight of sample
- <sup>#1</sup> = The total Lead limit for surface coatings and similar materials will be **90ppm** (Effective Date : August 14, 2009)
- <sup>#2</sup> = The total Lead limit for other materials will be **300ppm** (Effective Date : August 14, 2009)

Building C, Hongwei Industrial Zone, Baoan 70 District, Shenzhen

# Test Report

Report No.: SHT09011400125

Page 5 of 5

## Photo of the sample



\*\*\* End of report \*\*\*

This report is considered invalidated without the Special Seal for Inspection of the CTI, This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of CTI, this test report shall not be copied except in full and published as advertisement.

Building C, Hongwei Industrial Zone, Baoan 70 District, Shenzhen